

PROVINCIAL BIDS AND AWARDS COMMITTEE

SUPPLEMENTAL BID BULLETIN

TO: ALL PROSPECTIVE BIDDERS

This Supplemental Bid Bulletin is issued to amend **Section VI**— Specifications of the bid document published on September 17, 2025 under **PhilGEPS Reference No. 12381485**, for **Lot No. 1- Bid No. B20254127-** Procurement of 1 Lot Contract Package: Equipment, Labor and Materials for the Installation of Solar Street Lights along Bdry. Tagum - Baca - New Corella Provincial Road, Davao del Norte for the following details, viz;

- Tollowing details, viz,	
FROM	TO
SCOPE OF WORKS:	SCOPE OF WORKS:
PART I - OTHER GENERAL REQUIREMENTS	PART I - OTHER GENERAL REQUIREMENTS
B.5 - Project Billboard / Signboard: 1.00 each	B.5 - Project Billboard / Signboard: 1.00 each
B.7 - Occupational Safety and Health: 1.00 L.S.	B.7 - Occupational Safety and Health: 1.00 L.S.
B.9 - Mobilization/Demobilization: 1.00 lot	B.9 - Mobilization/Demobilization: 1.00 lot
PART III - CIVIL, MECHANICAL, ELECTRICAL AND	PART III - CIVIL, MECHANICAL, ELECTRICAL AND
Sanitary/Plumbing works	SANITARY/PLUMBING WORKS
PART D - ELECTRICAL WORKS	PART D - ELECTRICAL WORKS
1103 - Lighting Fixtures and Lamps (Solar Powered LED	1103 - Lighting Fixtures and Lamps (Solar Powered LED
Streetlights): 31.00 units	Streetlights): 31.00 units
Solar Powered LED Street Light, Integrated with Single	Solar Powered LED Street Light, Integrated with Single
Arm	Arm
• 60 W LED Lamp, 5050 LED type	60 W LED Lamp, 5050 LED type
 Luminous Flux: 11,400 lm, Daylight 	Luminous Flux: 11,400 lm, Daylight
Efficacy: 190 lm/W	Efficacy: 190 lm/W
 Dimension and weight: L1418 x W365 x H211 (mm) / 	 Dimension and weight: L1418 x W365 x H211 (mm)
19.66 kg \pm 1 kg (net weight)	<u>±20mm</u> / 19.66 kg ± 1 kg (net weight)
 Solar Panel: Mono Crystalline Silicon 18 V / 80 W 	Solar Panel: Mono Crystalline Silicon 18 V / 80 W
 Battery: Li-ion 12.8 V / 42 AH (537.6WH) 	• Battery: Li-ion 12.8 V / 42 AH (537.6WH)
 Auto day and night recognition control 	Auto day and night recognition control
Ingress Protection (IP) 65	Ingress Protection (IP) 65
• Single Arm: 50 mm ø x 2 m, G.I. Schedule 40, paint	• Single Arm: 50 mm ø x 2 m, G.I. Schedule 40, paint
finish with bracket and complete accessories	finish with bracket and complete accessories
(fabricated to complement with the existing utility	(fabricated to complement with the existing utility pole)
pole)	Mounting Height: 4 - 12 meters
 Mounting Height: 4 - 12 meters 	Warranty: 1 year
Warranty: 1 year	Beam Angle: Type II (155° x 60°)
• Beam Angle: Type II (155° x 60°)	CE - RoHS Certificate
CE - RoHS Certificate	Bifacial Integrated Solar Panels (Double-sided
Bifacial Integrated Solar Panels (Double-sided	Charging)
Charging)	Dimming: Time Scheduled + PIR
Dimming: Time Scheduled + PIR	100% (3H) + 70% (3H, PIR - 100%) + 50% (6H-PIR-100%)
100% (3H) + 70% (3H, PIR - 100%) + 50% (6H-PIR-100%)	Correlated Color Temperature: 5000K±500K

For guidance and information of all concerned.

Correlated Color Temperature: 5000K±500K

Color Rendering Index: greater than or equal to 70

Issued this 30TH day of September, 2025.

ATTY. RALPH P. DELA CRUZ, LT. COL., PA (RET)
Provincial Administrator
BAC Chairperson

Color Rendering Index: greater than or equal to 70